

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12438231
Catalog # : 00156ET3E143T-W22

Frame	: 143/5T	Locked rotor time	: 37s (cold) 21s (hot)
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 3.92/1.96 A	Protection degree	: IP55
L. R. Amperes	: 34.9/17.4 A	Cooling method	: IC411 - TEFC
LRC	: 8.9x(Code L)	Mounting	: F-1
No load current	: 1.66/0.830 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3480 rpm	Noise level ²	: 68.0 dB(A)
Slip	: 3.33 %	Starting method	: Direct On Line
Rated torque	: 2.24 ft.lb	Approx. weight ³	: 44.5 lb
Locked rotor torque	: 310 %		
Breakdown torque	: 370 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0470 sq.ft.lb		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	81.5	84.0	84.0	Max. traction	: 51 lb
Power Factor	0.68	0.78	0.84	Max. compression	: 96 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
17.7	13.3	12.1	9.8	5.6	3.8	2.4

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type	: 6205 ZZ	: 6204 ZZ
Sealing	: V'Ring	: V'Ring
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	


Notes
USABLE @208V 4.20A SF 1.15 SFA 4.83A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	11/03/2025			
			Page	Revision
			1 / 1	



MADE IN MEXICO
12438231



MODEL 00156ET3E143T-W22

Inverter Duty Motor
Severe Duty



Class I, Div 2, Gr A, B, C, D, 1.15SF - T3
Class II, Zone 2, IIC, 1.15SF - T3
Class II, Div 2, Gr F, G - T5
60Hz: For use on PWM: Gr. A, B, C, D, F,
G, VT 1000:1, CT 20:1, 1.00SF - T4A



FOR SAFE AREA
Mod.TE1BFOXON
CC029A

PH3 60Hz Fr. 143/5T 1000m.a.s.l. IP55 TEFC 44lb

V 230/460

A 3.92/1.96

HP 1.5

kW 1.1

SF 1.25

SFA 4.90/2.45

RPM 3480

PF 0.84



AMB 40°C

INS cl. F DT80K NEMA NOM EFF 84.0%

DUTY CONT.

DES B Code L

1.5HP 1.1kW 50Hz 380V 2.36A 2835RPM SF 1.25 SFA 2.95 EFF 81.5% (IE2)



MOBIL POLYREX EM

