

Gol Pumps Thechnology		DATA SHEET		Gol Pumps Technology INC	
		Thin Submersible Pump GOL PUMPS		3750 NW 114 Ave No: 6zip : 33178 Miami FL. USA	
		3" Inch Pump for 3.5" inch well		Tel: +1 (786) 615 - 8984 & (786) 452-9775 * Fax: +1*(786) 615-7043	
Pump Data Brand : GOL PUMPS Model : G3SD - M 2/28 Flow Rate: 5 GPM Head Rate: 560 FEET Head Max: 590 FEET Flow Max: 13 GPM RPM : 3450 rpm Normal Power P2 : 2 HP Fluid: Water Fluid Temperature: at about 25 °C. Density: water 1.0 kg/Dm³ Fluid Viscosity: 8.90 × 10⁻⁴ Pa-s With Float switch: NONE Kind of Workiny: Submersible Delivery size: 1 1/4" NPT Suction size: With Strainer Made in : CHINA		Motor Data Power P2: 1.5 KW Power P1: * Phase (PH): 1 Rate Voltage : 220 V Capacitor Need : 50/450 µF / V Ferequency : 60 Hz Rated Speed (rpm): 3450 rpm Current (A): 9.7 A Cos φ : 0.95 Degree of Protection (IP): IP 68 Safety Protection Included: F length of Cable : 2 M Kind of Plug : NONE Ambient Temp : 40°C = 104°F		Other Pump Data Impeller Size (mm) : * Pressuer Rating : PN 16 Min. Fluid Temp : 10°C = 50°F Max. Fluid Temp : 35°C = 95°F Ambient Temp : 40°C = 104°F Humidity % : 100%	
Special Specification Installation status : Vertical Variable frequency : NONE Solid Passage : 0.25%		Materials Pump Body : AISI 304 SS Support: AISI 304 SS Impeller: Plastic POM Mechanical Seal: Graphite/Ceramic Rubber: NBR Pump Shaft: AISI 304 SS Strainer: AISI 304 SS outer cover: Cast Iron Motor Case: AISI 304 SS		Shaft Seal Type: * Stationary Part: Ceramic Rotating Part: Graphite Elastomer: NBR	
Pump and Motor specification optional With Booster System: None With Complack: None Special Material: None Specail Voltage: None		Protection system required External Flout switch: NONE Minimum Starter: Over Load and Capacitor Box Include		Weight : 15 Kg Standard Approve CE	
		Applicant: For Water Supply from Wells or Reservoirs for Domestic Use for Civil and Industrial Applications for Garden Use and Irrigation		Dimention in mm P 779 M 543 T 1322 DN 1 1/4" D1 75 D2 73	

